

HUSH LAY 11



Hush Lay 11 is a high performing Dute felt underlay. This is used as a impact sound reducing layer for under carpets or solid timber flooring. Due to it's unique density Hush Lay 11 ensures the reduction of footfall noise transference from the final floor finish to the structure. This is a quick, simple and easy to install solution for domestic situations.

ACOUSTIC PERFORMANCE

Hush Lay 11 reduces the passage of impact sound from the carpet or timber final floor finish to the structure. Should be used as a simply underlay for domestic situations.



PRODUCT DATA

- Fibre Composition: Hair/Jute/Mixed Fibres (100% Recycled)
- Nominal Weight: 1695g/m² (+/- 5%) (500z/yd²)
- Nominal Thickness: 11.00mm (+/- 0.5mm)
- Roll Width: 1.37m
- Roll Length: 12.5m
- Standard Roll Area: 17.125m²
- Flame Retardancy: BS4790:1987 (Hot Metal Nut Test) Endurance FR achieves a 'low radius of effects of ignition' - no more than 20mm against maximum permitted of 35mm for low radius classification.
- Static Loading: BS4939 Thickness loss after 24 hours loading and 24 hours recovery: Retained FR50 56%

- Sound impact: BS2750 Part 8:1980 Weighted impact sound improvement 24db
- Thermal Resistance: BS3745 2.5 Togs
- All products held to stock

SUITABLE FOR:



Features

- ✓ Environmentally friendly
- ✓ It may be trimmed with scissors and is pleasant to handle, requiring no precautions against skin or respiratory irritation.

[VIEW ON OUR WEBSITE](#) ➔

HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: info@hushacoustics.co.uk

www.hushacoustics.co.uk

[in](#) hush-acoustics [ig](#) hushacoustics

[tw](#) @hushacoustics [f](#) hushuk.acoustics

44 Canal Street, Bootle, Liverpool L20 8QU

Offices also based in London and Yorkshire



HUSH ACOUSTICS
Sound Insulation Products and Systems